

Tamper-Resistant Bolts

Designated Parking Corp (DPC) has developed tamper resistant bolts that are used to secure barriers, furniture, racks and the like to walls and floors. The 8 millimeters (M8x1.25) bolts are compatible with DPC's line of masonry or asphalt anchors.

The bolts are tri-groove type with rounded and tapered heads. The taper makes it more difficult to grab the head with pliers or pipe wrenches. Added security can be achieved if the head is surrounded by a raised housing or a free-rotating cup washer, as shown above.



The bolts are chrome plated and come in a variety of lengths. A socket and wrench are available.

	length	Part No.	List \$
Bolt M8	10mm	41-4012	1.50
Bolt M8	13.5mm	41-4011	1.50
Bolt M8	14.5mm	41-4016	1.50
Bolt M8	18mm	41-4010	1.50
Bolt M8	32mm	41-4017	1.85
Bolt M8	46mm	41-4018	2.25
Socket	tri	51-6202	5.00
Wrench	M5	51-6204	2.50
CA6/7	60mm	01-6305.7	14.00



Tamper-resistant Bolt with matching wrench

Use with SP14 Asphalt Anchors


The bolts can be used with DPC's asphalt anchors, model SP14. See datasheet for details about the SP14 for details.



Please note that the thread in the SP14 is only 21 mm deep (0.85"). Therefore, the correct length of the bolt must be used so that the bottom of the bolt does not hit the bottom of the thread well in the SP14 anchor. It is best to prevent the bolt from penetrating more than 19 mm into the anchor.

Use with Masonry Anchors

DPC provides CA6 concrete/masonry anchors which accept M8 bolts. Use the built in cup bolts to tighten the anchor to the concrete, then replace the bolt with the 46mm security bolt.



The CA6/7 kit includes 7 anchors, washers and a wrench for the M8 cup bolts



10 Ridge Rd
West Orange, NJ 07052
USA

Tel: 1.973.669.8214
Fax: 1.973.669.5161
Email: info@dp-corp.com
WEB: www.dp-corp.com